

Organ Specification - St Mary's Church, Hexham

Great organ, 56 notes

1	Open Diapason	8	
2	Wald flute	8	
3	Principal	4	
4	Nazard	2 $\frac{2}{3}$	TC
5	Fifteenth	2	
6	Tierce	1 $\frac{3}{5}$	TC
7	Mixture	III	

Swell organ, 56 notes

8	Stopped diapason	8	
9	Salicional	8	1-7 from 8
10	Celeste	8	TC
11	Gemshorn	4	
12	Doublette	2	
13	Mixture	II-III	
14	Trumpet	8	

Pedal organ, 30 notes

15	Acoustic Bass	32	A, 1-12 A+B
16	Subbass	16	A
17	Leiblich Bourdon	16	B
18	Flute	8	A
19	Contra Fagotto	16	

Couplers - Gt-Ped, Sw-Ped, Sw-Gt.

Tremulant to Swell.

Tracker action to manuals, electric action to pedals and stop system.

Four divisional pistons to each manual, six general pistons, Gt-Ped reversible piston.

Multi-level memory capture system.

Wells-Kennedy Partnership, Lisburn, 1983.

Modifications by the Pipe Organ Preservation Company of Ireland, 2019.

Consultant - Paul Hale.

Modifications - splitting of Swell sesquialtera into separate nazard and tierce ranks on Great; addition of swell celeste in place of sesquialtera; addition of small-scale leiblich bourdon on separate chest and 32' resultant bass. Replacement of stop actions and solenoids and addition of solid state piston and capture system, reconfiguring casework for the corner gallery position.